



Valspar Chalky Finish Paint System

No. 87000 Series

GENERAL DESCRIPTION

Get the look without sanding or priming! Start with Chalky Finish Paint tinted to your selected color for an Ultra-Matte finish. Next, use Clear Sealing Wax for a Satin and/or Distressed look. Finish with Antiquing Wax, the last step to old-world charm.

GET THE LOOK: 3-STEP FINISH

- Chalky Finish Paint: Vintage chic for wood and metal furniture
- Sealing Wax: low-gloss protection perfects the look
- Antiquing Wax: last step to old-world charm

RECOMMENDED USES

Use on décor items and varnished, previously painted, bare wood or metal furniture.

COMPOSITION

Base and Fill Levels

	(oz./qt)
Medium Base (87000)	29
Deep Base (87001)	29
	(oz./pt)
Sealing Wax (87002)	16
Antiquing Wax (87003)	16

PRODUCT SPECIFICATIONS

VOC (g/L): less than 50 g/L

Weight Per Gallon: 10.3 lbs.

Practical Coverage: Covers approximately 75 to 150 sq. ft. (14–17 m²) per quart depending on porosity and application technique.

Dry Time @ 77 °F and 50% Relative Humidity

To the touch: 1–2 hours

Recoat: 4 hours

Washing instructions: Allow to cure 30 days before washing with a mild detergent and soft sponge.

Application Temperature: 50–90 °F (10–32 °C)

REGULATORY COMPLIANCE

Current as of: 12/17/2014

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

SURFACE PREPARATION

Priming and sanding is not necessary. Surface should be wiped clean of dust, loose dirt, grease etc.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Stir paint thoroughly. Apply with a premium-quality, polyester-bristle brush.

Begin with 1 coat of Valspar Chalky Finish Paint for a muted, distressed look. For full, rich color apply 2 coats. Multiple coats of different colors may be applied for a layered effect. Allow paint to dry thoroughly between coats.

Seal with a top coat of Valspar® Sealing Wax, or allow to wear naturally. Brush on a layer of Sealing Wax, wiping off excess, allow to dry. Gently sand thru layers along corners, edges and anywhere you wish to reveal previous layers.

For an antiqued patina, apply a layer of Valspar® Antiquing Wax, according to directions. For a general antique finish, brush a thinner coat on, let stand for 1–2 minutes and wipe off excess with a soft, lint-free cloth. To achieve a more worn look, brush on a thick coat of this product in the desired areas. Apply a final coat of Valspar® Sealing Wax if desired.

Visit us at valsparpaint.com/chalkyfinishpaint for additional tips and techniques.

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

LIMITED WARRANTY

This product is warranted to perform to your satisfaction at the time of application when applied to a properly prepared residential surface in accordance with the label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

CAUTION! KEEP OUT OF THE REACH OF CHILDREN. May cause eye and skin irritation. Use only with adequate ventilation. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY. First Aid: Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* If Inhaled: If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* If Swallowed: Drink 2 glasses of water. Get medical attention immediately.*
*Call poison control center, hospital emergency room or physician immediately.

UCL 1.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

8725 W. Higgins Rd., Chicago, IL 60631
877.825.7727

valsparpaint.com
Revised: 12/17/14
Version: 87000A

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.