

GENERAL DESCRIPTION

Valspar Cabinet Enamel dries to a smooth factory-finish and stands up to daily use. Old finishes are covered with little-to-no prep work. The oil-enriched formula is as durable as traditional oils but cleanup with soap and water and resists yellowing.

PREP FOR SUCCESS

Previously Painted Surfaces:

1. Read the Lead Warning Paragraph. Examine the surface and decide how to prepare it for painting.
 - If furniture is dusty, simply wipe down with soft, damp rag and let dry. If surface has heavy dirt, mildew, greasy or waxy residue, remove it with a mild household cleaner, rinse well and dry thoroughly.
 - If existing paint is peeling or chipping, remove it gently with a scraper. Sand the edges of the remaining paint to smooth the surface. Wipe away all sanding dust with a damp rag and dry thoroughly.
 - If you are painting a laminate or lacquered item with a smooth or glossy surface, rough up the surface with a medium medium-to to-fine grit sanding block. Wipe away all sanding dust with a soft, damp rag and dry thoroughly.
2. Remove hardware or cover any hardware you are unable to remove with tape.
3. Tape around anything that you don't want painted to achieve a crisp, clean line, such as inside edges of doors and drawers.

Visit valsparpaint.com/rehabproject for more tips

Bare Wood:

For best results, 3 coats may be required. Priming bare wood is not required.

Laminate or High-Gloss Surfaces:

Remove gloss from shiny surfaces with a medium-to-fine grit sand paper. For maximum adhesion, a coat of Valspar Bonding Primer is recommended.

Metal:

All bare metal surfaces should be primed with a rust-inhibitive metal primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION AND DRY TIME

Stir paint thoroughly. Do not thin. Inter-mix containers to ensure uniform color. Two thin coats are recommended for smooth even coverage. Allow to dry thoroughly before recoating. Apply with a premium-quality roller or polyester brush. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage.

Drying time: Dries to the touch in 4 hours; longer in high humidity or cool temperatures. Paint only when surface and air temperatures are 50–90 °F (10–32 °C). Allow to dry 8–12 hours before recoating. **The surface will feel dry after 24 hours, however the maximum performance for adhesion and hardness develop over time. To prevent scratches, marring, or peeling, allow the project to dry for a minimum of 3 days. Humidity and temperature will affect these suggested times.**

Washing Instructions: Allow at least 7 days before washing. Use mild detergent and sponge.

LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

REGULATORY COMPLIANCE

Current as of: 9/12/2017

| | |
|---------------|-----|
| SCAQMD | Yes |
| CARB 2000 SCM | Yes |
| CARB 2007 SCM | Yes |
| OTC/LADCO | Yes |
| US National | Yes |

PRODUCT SPECIFICATIONS

Vehicle Type: Alkyd-Acrylic Hybrid

Viscosity: 87–95 Krebs Units

Flashpoint: N/A

VOC (g/L): Less than 50 g/l 0.42 lb/gal as per 40 CFR 59.406

Weight Per Gallon: 11 lbs./gal.

Coverage: Covers up to 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity.

Packaging:

Quart – 4 per carton

Gallon – 4 per carton

Base and Size:

Base 1 (Q: 740158, G: 740159)

Base 4 (Q: 740162, G: 740163)

Fill Level:

124 oz./gal.

116 oz./gal.

CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.*
*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

8725 W. Higgins Rd., Chicago, IL 60631

888.313.5569

valsparpaint.com

Revised: 9/12/17