

# valsparPRO™ ValsparPRO® Contractor Coat Interior Latex Flat Paint

## No. 9447509 Series



### GENERAL DESCRIPTION

**Contractor Coat** delivers a great product at a great price. The acrylic formula provides good hide and coverage while making touch ups unnoticeable. This ValsparPRO® product is good for customers that need a quality product that brushes, rolls, and sprays uniformly for any type of property. Ideal for properly prepared interior walls, and ceilings, previously painted or bare drywall, plaster, masonry and primed metal.

### PRODUCT FEATURES

- Good hide & coverage
- Great touch-up
- Durable film
- Smooth, uniform finish
- Easy application spray, brush and roll

### RECOMMENDED USES

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal.

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

- Gallon – 4 per carton
- 5 gallon pail

### COMPOSITION

#### Base and Fill Levels

	(oz./gal.)
High Hiding White (9447509, 9447511)	128
Pastel Base (9447508, 9447510)	124
Neutral Base (9460040)	116

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, premium-quality synthetic brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage.

**Airless Spray:**

- Pressure: 2000 PSI
- Tip: 0.015"–0.021"

**Brush:** premium-quality synthetic

**Roller:** Premium-quality roller 3/8" nap

### SYSTEM

#### RECOMMENDATIONS

**Drywall/Wallboard (new):**

- 1 Coat: Valspar® Interior Drywall Primer-Sealer
- 1–2 Coats: Valspar® Contractor Coat Interior Latex Flat Paint

**Plaster:**

- 1 Coat: Valspar® Interior Drywall Primer-Sealer
- 1–2 Coats: Valspar® Contractor Coat Interior Latex Flat Paint

**New Wood/Composition Board:**

- 1 Coat: Valspar® Int/Ext Stainblocking Bonding Primer
- 1–2 Coats: Valspar® Contractor Coat Interior Latex Flat Paint

**Interior Concrete Block:**

- 1 Coat: Valspar® Block filler
- 1–2 Coats: Valspar® Contractor Coat Interior Latex Flat Paint

**Masonry:**

- 1 Coat: Valspar® Masonry and Stucco Primer
- 1–2 Coats: Valspar® Contractor Coat Interior Latex Flat Paint

**Previously Painted Surfaces:**

- 1–2 Coats: Valspar® Contractor Coat Interior Latex Flat Paint

Recommended one coat primer if the painting project requires a bold color transition. This will improve the topcoat hiding power.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Vinyl copolymer

**Pigment Type:** Titanium Dioxide

**Viscosity:** 97–107 Krebs Units

**Sheen:** 0–5 Units @ 85° angle

**Flashpoint:** N/A

**VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Volume Solids:** 38%

**Weight Solids:** 57%

**Weight Per Gallon:** 12.0 lbs./gal.

**Practical Coverage:** Covers up to 350–450 sq. ft. per gallon (32–42 m<sup>2</sup> per 3.78 L). Less on rough or porous surfaces. Thin with up to 8 oz. water per gallon only if paint is too thick for sprayer.

**Recommended Film Thickness:**

- 4.0 mil Wet      1.5 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 1 hour

**Recoat:** 4 hours

**Washing:** Allow at least 7 days before washing.

Use mild detergent and sponge.

**Application Temperature:** 50–90 °F (10–32 °C)

### CERTIFICATIONS

Current as of: 6/13/2018

UL Greenguard Gold	Yes
LEED (US)	Yes
LEED (Canada)	Yes

### REGULATORY COMPLIANCE

Current as of: 6/13/2018

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

### CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

# valspar<sup>PRO</sup>™ Valspar® Contractor Coat Interior Latex Flat Paint

---

## No. 9447509 Series

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all wax, grease, dirt, chalk, mildew, loose and peeling paint and other foreign matter. Remove gloss from shiny surfaces. Repair all cracks and nail holes with patching compound. Painting over wallpaper is not recommended. New or bare surfaces should be primed with an appropriate Valspar® primer.

#### **Drywall and Plaster:**

Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior Drywall Primer-Sealer

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior/Exterior Stainblocking Bonding Primer.

#### **Concrete Block:**

Concrete block surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust. Fill pores of bare concrete block with Valspar® Block filler, then top coat.

#### **Masonry:**

New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Prime bare surfaces with Valspar® Masonry and Stucco Primer, then top coat.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### CAUTIONS

Contains Crystalline Silica. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

16 (01/10)

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

#### **EMERGENCY MEDICAL TELEPHONE:**

**1-888-345-5732**

Valspar  
Cleveland, OH  
[valsparpaint.com](http://valsparpaint.com)  
888.313.5569  
VALPROCCTINTFLT